

**40/60 Versa-Lift with 0 Counterweight Slabs
and Side Shifting Carriage**

Slab Weight (lbs)
3750

Number of Slabs
0

Standard Wheel Base
98

| | | Lift Capacities w/Forks Only (lbs) | | | | |
|------------------------------------------------|----|-------------------------------------------|-------|-------|-------|-------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Fork Face (in) | 36 | 20000 | 22200 | 24300 | 26500 | 28700 |
| | 48 | 17000 | 18800 | 20600 | 22400 | 24200 |
| | 60 | 14700 | 16300 | 17900 | 19400 | 21000 |
| | 72 | 13000 | 14400 | 15800 | 17100 | 18500 |
| | 84 | 11600 | 12800 | 14100 | 15300 | 16600 |

| | | Lift Capacities w/Boom Only (lbs) | | | | |
|------------------------------------------------|-----|------------------------------------------|--------|--------|--------|--------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Boom Face (in) | 24 | 18500 | 20600 | 22700 | 24900 | 27000 |
| | 36 | 15700 | 17500 | 19300 | 21100 | 22900 |
| | 48 | 13600 | 15200 | 16700 | 18300 | 19900 |
| | 60 | 12000 | 13400 | 14800 | 16200 | 17600 |
| | 72 | 10800 | 12000 | 13300 | 14500 | 15700 |
| | 84 | 9800 | 10900 | 12000 | 13100 | 14200 |
| | 96 | 8900 | 9900 | 11000 | 12000 | 13000 |
| | 108 | 8200 | 9200 | 10100 | 11000 | 12000 |
| | 120 | 7600 | 16000* | 16000* | 16000* | 16000* |

| | | Lift Capacities w/Boom & Forks (lbs) | | | | |
|------------------------------------------------|----|-------------------------------------------------|-------|-------|-------|-------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Boom Face (in) | 24 | 17300 | 19400 | 21500 | 23600 | 25700 |
| | 36 | 14600 | 16400 | 18200 | 20000 | 21800 |
| | 48 | 12700 | 14300 | 15800 | 17400 | 19000 |
| | 60 | 11200 | 12600 | 14000 | 15400 | 16700 |
| | 72 | 10100 | 11300 | 12500 | 13800 | 15000 |

*All Load Capacities are Rated with the Mast Vertical
Capacities Marked '*' are Bound by Structural Limitations*

40/60 Versa-Lift with 1 Counterweight Slabs and Side Shifting Carriage

Slab Weight (lbs)
3750

Number of Slabs
1

Standard Wheel Base
98

| | | Lift Capacities w/Forks Only (lbs) | | | | |
|------------------------------------------------|----|-------------------------------------------|-------|-------|-------|-------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Fork Face (in) | 36 | 24600 | 27300 | 30000 | 32700 | 35400 |
| | 48 | 20800 | 23100 | 25400 | 27700 | 29900 |
| | 60 | 18000 | 20000 | 22000 | 24000 | 25900 |
| | 72 | 15900 | 17700 | 19400 | 21100 | 22900 |
| | 84 | 14200 | 15800 | 17400 | 18900 | 20500 |

| | | Lift Capacities w/Boom Only (lbs) | | | | |
|------------------------------------------------|-----|------------------------------------------|--------|--------|--------|--------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Boom Face (in) | 24 | 23000 | 25600 | 28300 | 31000 | 33600 |
| | 36 | 19500 | 21700 | 24000 | 26300 | 28500 |
| | 48 | 16900 | 18900 | 20800 | 22800 | 24800 |
| | 60 | 15000 | 16700 | 18400 | 20100 | 21900 |
| | 72 | 13400 | 14900 | 16500 | 18000 | 19600 |
| | 84 | 12100 | 13500 | 14900 | 16300 | 17700 |
| | 96 | 11100 | 12400 | 13600 | 14900 | 16200 |
| | 108 | 10200 | 11400 | 12600 | 13700 | 14900 |
| | 120 | 9400 | 16000* | 16000* | 16000* | 16000* |

| | | Lift Capacities w/Boom & Forks (lbs) | | | | |
|------------------------------------------------|----|-------------------------------------------------|-------|-------|-------|-------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Boom Face (in) | 24 | 21700 | 24400 | 27100 | 29700 | 32400 |
| | 36 | 18400 | 20700 | 22900 | 25200 | 27500 |
| | 48 | 16000 | 18000 | 19900 | 21900 | 23800 |
| | 60 | 14100 | 15900 | 17600 | 19300 | 21100 |
| | 72 | 12700 | 14200 | 15800 | 17300 | 18900 |

*All Load Capacities are Rated with the Mast Vertical
Capacities Marked '*' are Bound by Structural Limitations*

40/60 Versa-Lift with 2 Counterweight Slabs and Side Shifting Carriage

Slab Weight (lbs)
3750

Number of Slabs
2

Standard Wheel Base
98

| | | Lift Capacities w/Forks Only (lbs) | | | | |
|------------------------------------------------|----|-------------------------------------------|-------|-------|-------|-------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Fork Face (in) | 36 | 29100 | 32400 | 35600 | 38900 | 42100 |
| | 48 | 24600 | 27400 | 30100 | 32900 | 35600 |
| | 60 | 21400 | 23700 | 26100 | 28500 | 30900 |
| | 72 | 18800 | 20900 | 23000 | 25100 | 27200 |
| | 84 | 16900 | 18700 | 20600 | 22500 | 24400 |

| | | Lift Capacities w/Boom Only (lbs) | | | | |
|------------------------------------------------|-----|------------------------------------------|--------|--------|--------|--------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Boom Face (in) | 24 | 27500 | 30700 | 33900 | 37000 | 40200 |
| | 36 | 23300 | 26000 | 28700 | 31400 | 34100 |
| | 48 | 20200 | 22600 | 24900 | 27300 | 29600 |
| | 60 | 17900 | 19900 | 22000 | 24100 | 26200 |
| | 72 | 16000 | 17900 | 19700 | 21600 | 23400 |
| | 84 | 14500 | 16200 | 17900 | 19500 | 21200 |
| | 96 | 13200 | 14800 | 16300 | 17900 | 19400 |
| | 108 | 12200 | 13600 | 15000 | 16400 | 17900 |
| | 120 | 11300 | 16000* | 16000* | 16000* | 16000* |

| | | Lift Capacities w/Boom & Forks (lbs) | | | | |
|------------------------------------------------|----|-------------------------------------------------|-------|-------|-------|-------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Boom Face (in) | 24 | 26200 | 29400 | 32600 | 35800 | 39000 |
| | 36 | 22200 | 24900 | 27700 | 30400 | 33100 |
| | 48 | 19300 | 21700 | 24000 | 26400 | 28700 |
| | 60 | 17100 | 19100 | 21200 | 23300 | 25400 |
| | 72 | 15300 | 17100 | 19000 | 20900 | 22700 |

*All Load Capacities are Rated with the Mast Vertical
Capacities Marked '*' are Bound by Structural Limitations*

40/60 Versa-Lift with 3 Counterweight Slabs and Side Shifting Carriage

Slab Weight (lbs)
3750

Number of Slabs
3

Standard Wheel Base
98

| | | Lift Capacities w/Forks Only (lbs) | | | | |
|------------------------------------------------|----|-------------------------------------------|-------|-------|-------|-------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Fork Face (in) | 36 | 33700 | 37500 | 41300 | 45000 | 48800 |
| | 48 | 28500 | 31700 | 34900 | 38100 | 41300 |
| | 60 | 24700 | 27500 | 30300 | 33000 | 35800 |
| | 72 | 21800 | 24200 | 26700 | 29100 | 31600 |
| | 84 | 19500 | 21700 | 23900 | 26100 | 28300 |

| | | Lift Capacities w/Boom Only (lbs) | | | | |
|------------------------------------------------|-----|------------------------------------------|--------|--------|--------|--------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Boom Face (in) | 24 | 31900 | 35700 | 39400 | 43100 | 46900 |
| | 36 | 27100 | 30300 | 33400 | 36600 | 39800 |
| | 48 | 23500 | 26300 | 29000 | 31800 | 34500 |
| | 60 | 20800 | 23200 | 25600 | 28100 | 30500 |
| | 72 | 18600 | 20800 | 23000 | 25100 | 27300 |
| | 84 | 16800 | 18800 | 20800 | 22800 | 24700 |
| | 96 | 15400 | 17200 | 19000 | 20800 | 22600 |
| | 108 | 14200 | 15800 | 17500 | 19100 | 20800 |
| | 120 | 13100 | 16000* | 16000* | 16000* | 16000* |

| | | Lift Capacities w/Boom & Forks (lbs) | | | | |
|------------------------------------------------|----|-------------------------------------------------|-------|-------|-------|-------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Boom Face (in) | 24 | 30700 | 34400 | 38200 | 41900 | 45600 |
| | 36 | 26000 | 29200 | 32400 | 35500 | 38700 |
| | 48 | 22600 | 25300 | 28100 | 30800 | 33600 |
| | 60 | 20000 | 22400 | 24800 | 27300 | 29700 |
| | 72 | 17900 | 20100 | 22200 | 24400 | 26600 |

*All Load Capacities are Rated with the Mast Vertical
Capacities Marked '*' are Bound by Structural Limitations*

40/60 Versa-Lift with 4 Counterweight Slabs and Side Shifting Carriage

Slab Weight (lbs)
3750

Number of Slabs
4

Standard Wheel Base
98

| | | Lift Capacities w/Forks Only (lbs) | | | | |
|------------------------------------------------|----|-------------------------------------------|-------|-------|-------|-------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Fork Face (in) | 36 | 38200 | 42600 | 46900 | 51200 | 55600 |
| | 48 | 32300 | 36000 | 39700 | 43300 | 47000 |
| | 60 | 28000 | 31200 | 34400 | 37600 | 40700 |
| | 72 | 24700 | 27500 | 30300 | 33100 | 36000 |
| | 84 | 22100 | 24600 | 27100 | 29700 | 32200 |

| | | Lift Capacities w/Boom Only (lbs) | | | | |
|------------------------------------------------|-----|------------------------------------------|--------|--------|--------|--------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Boom Face (in) | 24 | 36400 | 40700 | 45000 | 49200 | 53500 |
| | 36 | 30900 | 34500 | 38100 | 41800 | 45400 |
| | 48 | 26800 | 30000 | 33100 | 36200 | 39400 |
| | 60 | 23700 | 26500 | 29200 | 32000 | 34800 |
| | 72 | 21200 | 23700 | 26200 | 28700 | 31200 |
| | 84 | 19200 | 21500 | 23700 | 26000 | 28200 |
| | 96 | 17600 | 19600 | 21700 | 23700 | 25800 |
| | 108 | 16200 | 18100 | 19900 | 21800 | 23700 |
| | 120 | 15000 | 16000* | 16000* | 16000* | 16000* |

| | | Lift Capacities w/Boom & Forks (lbs) | | | | |
|------------------------------------------------|----|-------------------------------------------------|-------|-------|-------|-------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Boom Face (in) | 24 | 35200 | 39400 | 43700 | 48000 | 52300 |
| | 36 | 29800 | 33500 | 37100 | 40700 | 44300 |
| | 48 | 25900 | 29000 | 32200 | 35300 | 38500 |
| | 60 | 22900 | 25700 | 28400 | 31200 | 34000 |
| | 72 | 20500 | 23000 | 25500 | 28000 | 30400 |

*All Load Capacities are Rated with the Mast Vertical
Capacities Marked '*' are Bound by Structural Limitations*